

Road Force® - 5' Wide Standards

- Plywood Interior Sidewall Liner
- Undercoated Exterior Grade Plywood Floor
- Drip Rail
- Double Rear Doors with Full Length Aluminum Anti-Rack Cam Bar
- Stainless Steel Lockable Hasp
- Prefinished Aluminum Roof & Cove
- Fiberglass Front Cap
- D.O.T. Exterior Lighting & Reflectors
- 5-Bolt E-Coated Silver Spoke Wheel
- 15" Tires
- Aluminum Fenders
- Sealed Beam Tail Lights & Clearance Lights
- Tubular Steel Main Rails
- Undercoating on Complete Chassis
- Torflex Axles with EZ Lube Hubs
- Lighted License Plate Holder
- Tongue Jack with Sand Pad
- D.O.T. Safety Chains

Road Force® - 5' Wide Specifications

MODEL	RF581
BODY LENGTH	8'3"
BODY WIDTH	5'0"
OVERALL LENGTH	11'10"
OVERALL WIDTH (Includes Fenders)	6'9"
OVERALL HEIGHT	6'7"
INTERIOR LENGTH	8'0 1/2"
INTERIOR WIDTH	4'10"
INTERIOR HEIGHT	4'11"
PLATFORM HEIGHT	18"
AXLES	Single
AXLE TYPE	4" Drop
SUSPENSION	Torflex
TIRE SIZE	15"
LOAD RANGE	C
WHEEL BOLT PATTERN	5-Bolt/4.5
HITCH BALL SIZE	2"
HITCH TO TOP OF BALL	16"
HITCH WEIGHT (% OF CURB WEIGHT)	10-15%
CURB WEIGHT(LB.)	790
GVWR(LB.)	2200
GAWR(LB.)	2000
AVG. PAYLOAD	1410

CAPACITY(LB.)	
CUBIC CAPACITY (CUBIC FT.)	191
REAR DOORS	Double
REAR DOORS OPENING WIDTH	50"
REAR DOORS OPENING HEIGHT	53"
12 VOLT END CONNECTOR	4-way
Electric Brakes	No

Specifications subject to change.

Road Force® - 5' Wide Options

- Stabilizer Jacks
- Swing-Away Jack
- Side Door
- Rear Ramp Door
- Extruded Aluminum Ramp Extension
- Access Doors
- Radius Tinted Windows
- Slider Windows with Screen
- Floor Mounted D-Rings
- Wall Mounted Tie-Offs
- E-Track and F-Track
- 3/4" Wolmainzed Flooring
- Aluminum Tread Plate Flooring
- Aluminum Tread Plate Runners
- Vinyl Flooring
- White (or Gray) Vinyl Sldewalls & Ceiling
- Ceiling and Wall Insulation
- 12-volt Dome Light(s)
- 12-volt Porch Light(s)
- Fluorescent Lighting
- 14" x 14" Roof Vent with fan
- Side Vents
- 6 Circuit 12-volt Fuse Panel
- LED Clearance Lights and LED Tail Lights
- High Profile Brake Light
- 15 AMP/30 AMP/50 AMP 120 Volt Power Supply
- Duplex Receptacle (GFI also)
- ATP Stone Guard
- ATP Fenders
- Cover Rear End in Anodized Aluminum
- Roof Rack
- Nose Cone®
- AlumaSport Wheels
- Spare Tire Carrier
- Spare Tire/Wheel

Road Force® - 5' Wide Packages

SIDE DOOR PACKAGE

- 30", 36" or 48" Side Door with Full-Length Cam Lock
- 12 Volt Dome Light
- Wall Switch for Dome Light
- ATP Stone Guard (16" High)

RAMP DOOR PACKAGE

- Rear Ramp Door with Spring Assist & Stabilizer Jacks
- Wells Cargo Sidewall Vents (2)
- 12 Volt Dome Light
- Wall Switch for Dome Light

BASIC ELECTRICAL PACKAGE

- 15 Amp, 120 Volt Electric Power Supply for Extension Cord Hook-Up
- 15 Amp, Duplex 120 Volt Receptacle
- 4' Double Fluorescent Fixture
- Wall Switch for Fluorescent Light

DELUXE ELECTRICAL PACKAGE

- 30 Amp 120 Volt Service Panel with 30 Amp Main Breaker, 25' Shoreline & Locking Cable Hatch
- 15 Amp, Duplex 120 Volt Receptacles (3)
- 4' Double Fluorescent Fixtures (2)

Road Force® - 5' Wide Skin Colors



Road Force® - 6' Wide Standards

- Plywood Interior Sidewall Liner
- Undercoated Exterior Grade Plywood Floor
- Drip Rail
- Double Rear Doors with Full Length Aluminum Anti-Rack Cam Bar
- Stainless Steel Lockable Hasp
- Prefinished Aluminum Roof & Cove
- Fiberglass Front Cap
- D.O.T. Exterior Lighting & Reflectors
- 5-Bolt E-Coated Silver Spoke Wheel
- 15" Tires
- Aluminum Fenders
- Sealed Beam Tail Lights & Clearance Lights
- Tubular Steel Main Rails
- Undercoating on Complete Chassis
- Torflex Axles with EZ Lube Hubs
- Lighted License Plate Holder
- Tongue Jack with Sand Pad
- D.O.T. Safety Chains

Road Force® - 6' Wide Specifications

MODEL	RF6101	RF6121	RF6122
BODY LENGTH	10'0"	12'0"	12'0"
BODY WIDTH	6'0"	6'0"	6'0"
OVERALL LENGTH	14'1"	16'1"	16'1"
OVERALL WIDTH	7'9"	7'9"	7'9"
OVERALL HEIGHT	7'8"	7'8"	7'8"
INTERIOR LENGTH	9'9 1/2"	11'9 1/2"	11'9 1/2"
INTERIOR WIDTH	5'10"	5'10"	5'10"
INTERIOR HEIGHT	6'0"	6'0"	6'0"
PLATFORM HEIGHT	18"	18"	18"
AXLES	Single	Single	Tandem
AXLE TYPE	4" Drop	4" Drop	4" Drop
SUSPENSION	Torflex	Torflex	Torflex
TIRE SIZE	15"	15"	15"
LOAD RANGE	C	C	C
WHEEL BOLT PATTERN	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5
HITCH BALL SIZE	2"	2"	2 5/16"
HITCH TO TOP OF BALL	16"	16"	16"
HITCH WEIGHT (% OF CURB WEIGHT)	10-15%	10-15%	10-15%
CURB WEIGHT(LB.)	980	1180	1540
GVWR(LB.)	2990	2990	7000

GAWR(LB.)	2990	2990	7000
AVG. PAYLOAD CAPACITY(LB.)	2010	1810	5460
CUBIC CAPACITY (CUBIC FT.)	342	412	412
REAR DOORS	Double	Double	Double
REAR DOORS OPENING WIDTH	62"	62"	62"
REAR DOORS OPENING HEIGHT	65"	65"	65"
12 VOLT END CONNECTOR	4-way	4-way	7-way
ELECTRIC BRAKES (with Wet Cell Battery)	No	No	Yes

Specifications subject to change.

Road Force® - 6' Wide Options

- Stabilizer Jacks
- Swing-Away Jack
- Side Door
- Rear Ramp Door
- Extruded Aluminum Ramp Extension
- Access Doors
- Radius Tinted Windows
- Slider Windows with Screen
- Floor Mounted D-Rings
- Wall Mounted Tie-Offs
- E-Track and F-Track
- 3/4" Wolmainzed Flooring
- Aluminum Tread Plate Flooring
- Aluminum Tread Plate Runners
- Vinyl Flooring
- White (or Gray) Vinyl Sidewalls & Ceiling
- Ceiling and Wall Insulation
- 12-volt Dome Light(s)
- 12-volt Porch Light(s)
- Fluorescent Lighting
- 14" x 14" Roof Vent with fan
- Side Vents
- 6 Circuit 12-volt Fuse Panel
- LED Clearance Lights and LED Tail Lights
- High Profile Brake Light
- 15 AMP/30 AMP/50 AMP 120 Volt Power Supply
- Duplex Receptacle (GFI also)
- ATP Stone Guard
- ATP Fenders
- Cover Rear End in Anodized Aluminum
- Roof Rack
- Nose Cone®
- AlumaSport Wheels
- Spare Tire Carrier
- Spare Tire/Wheel

Road Force® - 6' Wide Packages

SIDE DOOR PACKAGE

- 30", 36" or 48" Side Door with Full-Length Cam Lock
- 12 Volt Dome Light
- Wall Switch for Dome Light
- ATP Stone Guard (*16" High*)

RAMP DOOR PACKAGE

- Rear Ramp Door with Spring Assist & Stabilizer Jacks
- Wells Cargo Sidewall Vents (*2*)
- 12 Volt Dome Light
- Wall Switch for Dome Light

BASIC ELECTRICAL PACKAGE

- 15 Amp, 120 Volt Electric Power Supply for Extension Cord Hook-Up
- 15 Amp, Duplex 120 Volt Receptacle
- 4' Double Fluorescent Fixture
- Wall Switch for Fluorescent Light

DELUXE ELECTRICAL PACKAGE

- 30 Amp 120 Volt Service Panel with 30 Amp Main Breaker, 25' Shoreline & Locking Cable Hatch
- 15 Amp, Duplex 120 Volt Receptacles (*3*)
- 4' Double Fluorescent Fixtures (*2*)
- Wall Switch for Fluorescent Lights

SAFETY PACKAGE

- Spare Tire & Wheel
- Spare Tire Carrier
- Spare Tire Cover
- High Profile Brake Light
- Fender Mounted Turn Indicator

BASIC LINER PACKAGE

- 1/4" White Vinyl Plywood Sidewall Liner
- 1/4" White Vinyl Plywood Ceiling Liner (*Curved*)
- Cover Front Cap
- Insulate Ceiling & Ends

DELUXE LINER PACKAGE

- 1/4" White Vinyl Plywood Sidewall Liner
- 1/4" White Vinyl Plywood Ceiling Liner (*Curved*)
- Cover Front Cap
- Insulate Sidewall, Ceiling & Ends
- B/W Checked Floor Linoleum

PREMIUM LINER PACKAGE

- 1/4" White Vinyl Plywood Sidewall Liner
- 1/4" White Vinyl Plywood Ceiling Liner (*Curved*)
- Cover Front Cap
- Insulate Sidewall, Ceiling & Ends
- Aluminum Diamond Tread Floor

MOTORCYCLE PACKAGE

- Removable Chrome Wheel Chock (*1*)
- 1" x 6' Ratchet Cycle Tie-Down Straps (*4*)
- Flush Mounted Sidewall Tie-offs (*2*)
- 5000 lb. Floor Tie-offs (*4*)
- Roof Vent (*14" x 14"*)

MOTORCYCLE PACKAGE

- Cover Rear End with Anodized Aluminum
- Upgrade from standard Tires/Wheels to Radial Tires & AlumaSport Wheels

Road Force® - 6' Wide Skin Colors



Warranty

Duration of Warranty

Your Road Force equipment, which has been manufactured, tested and inspected in accordance with carefully specified engineering requirements is warranted to the original owner to be free from defects in material and workmanship for the period of three (3) years, except as herein limited, from date of purchase. The obligation of this Warranty shall be limited to repairing or replacing any part or parts which, in the opinion of the Company, shall be proved defective in materials or workmanship under normal use and service during the three (3) year period commencing with the date of purchase. Jack rams, electrical wiring, glass, sealants, doors, seals, locks, paint, plumbing, couplers and jacks are warranted for a period of one (1) year from date of purchase.

This Warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Limitations and Exclusions

This Warranty shall NOT extend to:

1. Road Force equipment which has been modified, repaired, or altered in any way without the express written consent of Wells Cargo.
2. Unreasonable use (including failure to provide reasonable and necessary maintenance).
3. Tires, axles, axle assemblies, suspension components, ranges, heaters, refrigerators, air conditioners or all other appliances or components of the Road Force equipment which are warranted separately by the respective manufacturers of said components. These warranties are contained in your owners packet.
4. Any consequential damages for breach of this or any other warranty expressed or implied whatsoever. Repair or replacement under this Warranty is the exclusive remedy of the customer. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.
5. Parts not supplied by the Road Force manufacturer -- Wells Cargo.
6. Certain parts which require replacement in the ordinary course of use to normal wear.

Procedure

To secure repair of a Road Force trailer or any warranted parts under this Warranty, the unit or warranted part must be delivered, charges prepaid, to the nearest Wells Cargo manufacturing facility or as directed by Wells Cargo.

Your Road Force dealer from whom you purchased your unit is responsible for the registration of your warranty with the factory. We ask that you cooperate with your dealer in supplying the necessary information completing the warranty card so that we may better serve you.